



























NB: The portrayed colours may differ from reality.

References KAL04.. Composition: mixture of cellulose, polyester and sisal fibers. Weight \pm 146 g/m² (\pm 4,26 oz/sq yd) The wallcovering can be installed horizontally or vertically. Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Spongeable during installation.



Washable after installation.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



The mark of responsible forestry























KAL1110

KAL1111

KAL1118

KAL1117

KAL1107

KAL1108

KAL1112





KAL1116



NB: The portrayed colours may differ from reality.

References KAL11.. Composition: mixture of cellulose and polyester Weight: ± 196 g/m² (± 5,72 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (± 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Spongeable during installation.



Washable after installation.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Breathable.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



complying with the council directive 2014/90/ EU on marine equipment



The mark of sponsible forestry







NB: The portrayed colours may differ from reality.

References KAL2... Composition: mixture of cellulose and polyester Weight: ± 184 g/m² (± 5,37 oz/sq yd) Custom colouring on request.



Width of the wallcovering: $100 \text{ cm} (\pm 39^{\prime\prime} 1/3).$



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test6-7.



KAL21-22-26-28.. Washable after installation.



KAL20.. Extra washable.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Breathable.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment



The mark of responsible forestry





























NB: The portrayed colours may differ from reality.

References KAL38.. Composition: mixture of cellulose, polyester and sisal fibres Weight: ± 146 g/m² (± 4,26 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Washable after installation.



This design requires reverse hanging.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



The mark of responsible forestry





























NB: The portrayed colours may differ from reality.

References KAL4... Composition: mixture of cellulose and polyester Weight: ± 188 g/m² (± 5,48 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test6-7.



Spongeable during installation.



Washable after installation.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Breathable.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment

































NB: The portrayed colours may differ from reality.

References KAL56..

Composition: mixture of cellulose and polyester

Weight: ± 188 g/m² (± 5,48 oz/sq yd)
The wallcovering can be installed horizontally or vertically.

Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Washable after installation.



This design requires reverse hanging.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment



The mark of responsible forestry





























NB: The portrayed colours may differ from reality.

References KAL6... Composition: mixture of cellulose and polyester Weight: ± 184 g/m² (± 5,37 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Washable after installation.



This design requires reverse hanging.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment



The mark of responsible forestry





























NB: The portrayed colours may differ from reality.

References KAL75.. Composition: mixture of cellulose and polyester Weight: ± 196 g/m² (± 5,72 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (\pm 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Extra washable.



This design requires reverse hanging.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment



The mark of responsible forestry



































NB: The portrayed colours may differ from reality.

References KAL83.. Composition: mixture of cellulose and polyester. Weight \pm 196 g/m² (\pm 5,72 oz/sq yd) The wallcovering can be installed horizontally or vertically. Custom colouring on request.



Width of the wallcovering: 100 cm (± 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Spongeable during installation.



Washable after installation.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Breathable.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



complying with the council directive 2014/90/ EU on marine equipment



The mark of sponsible forestry





























KAL9401

NB: The portrayed colours may differ from reality.

References KAL94.. Composition: mixture of cellulose and polyester Weight: ± 196 g/m² (± 5,72 oz/sq yd) Custom colouring on request.



Width of the wallcovering: 100 cm (± 39" 1/3).



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant: EU: B, s1-d0 US: class A



Light resistant: Xeno test 6-7.



Washable after installation.



This design requires reverse hanging.



Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Sold by cut length.



Manufactured with recycled fibres.



Printed with solar energy.



Ecological.



Product complying with the council directive 2014/90/ EU on marine equipment



The mark of responsible forestry