

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
MATIERE	CUERO	FT N° 74 V1

This is a through-coloured PVC wallcovering, printed using water-based inks, on a high-tear non-woven backing. Extra washable and impact resistant, this Type II vinyl is suitable for intensive use in public buildings. In line with regulations, it has B s2 d0 / Class A fire resistance rating. Quick and easy to hang. Simply paste the wall and align the edges of each strip.

Description

Item code	CUEO 9150... / CUEO 9151...
Name	CUERO
Range	MATIERE
Type	PVC wallcovering
Plain	Yes - 23 colours
Patterned	No

Composition

Type	Compact PVC / Vinyl Type II
Backing	High-tear non-woven backing
Weight	450 g/m ²
Thickness	0.55 mm
Ink	Water-based printing inks

Regulations - Environment

Fire rating	B s2 d0 / Class A	EN 13501 / ASTM E-84
Acoustics	Alpha w = 0,10 or 0,15 according to the substrate / acoustic report: PEUTZ - N°A3151	
Light fastness	≥ 7	ISO 105
VOCs	A+	ISO 16000
CE marking	DOP-CPR-NTLBN-26 / www.texdecor.com	Norme EN 15 102
Manufactured by	ISO 14001	
Component	PVC with no phthalate	
Care	Extra washable - scrubbable	Standard EN 259
Use	Intensive	Standard EN 259

Packing - Packaging

Size of widths	106 cm +/- 3%
Length of roll	25 lm
Partial sale to order	Yes
Box size	145 X 21,5 X 23 cm = 25 ml
Weight of a roll	13 Kg (+/- 10%)

Hanging

Adhesive	Ovalit TM - Quelyd Murale	MSDS available
Adhesive instructions	Apply to the wall, using a roller	
Quantity of adhesive	+/- 200gr/m ²	
Match	Free match	
Hanging direction	Invert strips	
Seam	Butt seam or double cut overlap	
Removal	Pelable	