


TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 ACOUSTIC	QUICKMOUSSE Tweed	FT N°72 V1

This is a core dyed foam PVC acoustic wallcovering, printed using water-based inks, on non-woven backing. Washable and scrubbable, this wallcovering is suitable for intensive use in public buildings. In line with regulations, it has M1 and C s2 d0 fire resistance rating. Quick and easy to hang. Simply paste the wall.

Description

Item code	TWEE 9145
Name	Quickmousse
Range	Acoustic 0.3
Type	PVC wallcovering
Plain	Yes - 14 colours
Patterned	No

Composition

Type	PVC foam
Backing	Non-woven backing
Weight	580 g/m ²
Thickness	1,00 mm
Ink	Water-based printing inks

Regulations - Environment

Fire rating	C s2 d0 / M1	Standard EN 13 501 -1
Acoustics	Alpha w = 0.15 / NRC 0.1	Standard EN 20 354 / ASTM-C423-90a
Light fastness	≥ 7	Standard EN 259
VOCs	A+	ISO 16000
CE marking	DOP-CPR-PVCBN-24 / www.texdecor.com	Norme EN 15 102
Manufactured by	ISO 14001	
Component	PVC with no phthalate	
Care	Extra washable - scrubbable	Standard EN 259

Packing - Packaging

Size of widths	+/- 106 cm
Length of roll	30 lm - 15 lm
Partial sale to order	No
Dispenser box	FSC Certified Cardboard
Box size	110 X 27 X 30 cm for 30 lm
Weight of a roll	19,5 Kg (+/- 10%)

Hanging

Adhesive	Ovalit TM (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	+/- 250gr/m ²
Match	Free match
Hanging direction	Invert strips
Seams	Overlap seams
Removal	Strippable