

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
ACOUSTIC	VINACOUSTIC Tivoli	FT N° 46 V1

Standard EN 13 501 -1

Standard EN 20 354

Standard EN 12 667

Standard EN 15 102

Oeko-tex standard 100

Standard EN 259

Standard EN 259

Standard EN 259 LRV Scale

ISO 16000

ISO 1421

ISO 9002

NF ISO 105

This is a PVC foam wallcovering that is dyed in the mass, micro-perforated, printed with waterbased ink, on an Alpha 0.25 acoustic non-woven backing. Highly washable and brushable, resistant to impacts and scratches, this wall covering is particularly well-suited for intensive use in commercial and public establishments. In accordance with regulations, it has a M1 and Cs3d0 fire rating. Quick and easy to hang by simply pasting on the wall and hanging the strips edge to edge.

Description

9054 Item code

Vinacoustic Tivoli Name Range Acoustic

Type PVC wallcovering Plain Yes - 16 colours

Patterned

Composition

PVC Type

Backing Acoustic non-woven polyester

Weight 890 g/m² **Thickness** 3,5 mm

Ink Water-based printing inks

Treatment Bio-Pruf treatment on request > 500ml

Regulations - Environment

Fire rating C s3 d0 / M1 Acoustics Alpha w = 0.25

Light fastness

L.R.V rate Light reflectance value (85 max) Thermal resistance $R = 0.08 \text{ m}^2.\text{K/W}$

VOCs A+ Yes

CE marking Washable srubbable Care Use Intensive

daN: L>35 / T >30 Breaking strength Color fastness to rubbing dry 5/4 - wet 5/4 Certification

Manufactured by a certified factory

Packing - Packaging

Size of widths +/- 1.30m

Length of roll 25ml - 15ml - 10ml Partial sale to order No

Dispenser box Yes

FSC Certified Cardboard Suspended core packaging Yes

1450 X 350 X3 50 cm = 25ml ,15ml / 1450 X 215 X 230 cm = 10ml Box size Weight of a roll 31,22 Kg = 25ml, 19,65 Kg = 15ml, 13,87 Kg = 10ml. (+/- 10%)

Hanging operation

Adhesive Ovalit TM - Ovalit S (Metylan - Henkel)

Adhesive instructions Apply to the wall, using a roller

Quantity of adhesive +/- 300-450 gr/m² Match Free match Hanging direction Straight strips Seams Edge to edge seams Removal Dampen before stripping For partitions Yes - 130cm width

Demo video

