

## Specifications

Specifications:	Performance:
Weight (Avg):	15 oz/ly (339 gr/m <sup>2</sup> )
Width:	137 cm
Backing:	Scrim
Installation:	Reverse hang / Random match

Custom colors, weights, widths and microventing are available.

### Fire Safety:

- Class "A" Fire rated-Tested in accordance with ASTM E-84 Tunnel Test
  - Passes Class "A" NFPA 101 Life Safety Code
  - Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

### Environmental and Health:

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
  - Certified to NSF/ANSI 342 Sustainability Assessment
- Meets California Section 01350 IAQ test requirements for wall covering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

### USGBC LEED Support:

- MR – Materials and Resources – Construction waste management
- EQ – Indoor Environmental Quality – Low emitting materials

### Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

### Warranty:

J. Josephson is guaranteed to be free of defects in workmanship and material for five years.