

# TOWER

## MARQUISE SILK

54"/TYPE II/20 oz. **LOW VOC** **RECYCLED CONTENT**

### Physical Properties

WEIGHT	20 oz. PLY/620 G/PLM	13.3 oz.PSY G/PSM
WIDTH	54"/137 cm	
BACKING	Osnaburg	
MATCH	Reverse, random	

Custom colors, weights and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

### Fire Safety

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

### Environment & Health

- Contains 10% recycled content
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials

### Antimicrobial Features

TOWER wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate behind the walls. All TOWER wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

### Warranty

5 year warranty against manufacturing defects. Additional information is available at [www.towerwallcovering.com](http://www.towerwallcovering.com)

J•JOSEPHSON



NGC Nafees Wallpaper Co. LLC | PO Box 97035 | Dubai, UAE  
Tel: 971 4 269 7272 | Email: [sales@ngcmiddleeast.com](mailto:sales@ngcmiddleeast.com)

[ngcmiddleeast.com](http://ngcmiddleeast.com)