

TECHNICAL SPECIFICATION

	CONSTRUCTION		ELITE	DELUXE
	MACHINE GAUGE		1/8th Gauge Cut Pile Twist	1/8th Gauge Cut Pile Twist
	PILE HEIGHT	ISO 1766	7.5 mm	9 mm
	TUFT DENSITY	ISO 1763	120,899 tufts/m ²	130,199 tufts/m ²
	PILE WEIGHT		1,525 gms/m ²	1,864 gms/m ²
			45 oz/yd ²	55 oz/yd ²
	TOTAL CARPET WEIGHT	ISO 8543	2,462 gms/m ²	2,801 gms/m ²
	CARPET THICKNESS	ISO 1765	10.5 mm	12 mm
	WIDTH		4 & 5 metre	4 & 5 metre
	COMPOSITION			
	PILE CONTENT	ISO 1833	80% Wool, 10% Nylon, 10% Tuftbond Polyester	80% Wool, 10% Nylon, 10% Tuftbond Polyester
	PRIMARY BACKING		Woven Polypropylene	Woven Polypropylene
	SECONDARY BACKING		Woven Secondary	Woven Secondary
	PERFORMANCE			
	SUITABILITY		Extra Heavy Domestic	Extra Heavy Domestic / Medium Contract
	WIRA ABRASION TEST	PD 6527: Clause 17	Exceeds 24,000 Rubs	Exceeds 24,000 Rubs
	STATIC LOADING	ISO 3416	27.1% Thickness Loss after 24 hrs recovery	22.9% Thickness loss after 24 hrs recovery
	DYNAMIC LOADING	ISO 2094	29.2% Thickness Loss after 1,000 impacts	22.1% Thickness loss after 1,000 impacts
	TUFT ANCHORAGE	ISO 4919	Above 1.2 kg	Above 1.2 kg
	COLOUR FASTNESS			
	LIGHT FASTNESS	ISO 105-B02	5/6 on all colours	5/6 on all colours
	WET FASTNESS	ISO 105-E01	4/5 on all colours	4/5 on all colours
	SHAMPOO FASTNESS	BS 1006: UK-TB	4/5 on all colours	4/5 on all colours
	THERMAL VALUE			
	TOG VALUE	ISO 5085-1	1.3 Tog	1.3 Tog
	THERMAL RESISTANCE		0.13 m ² k/w	0.13 m ² k/w
	FLAMMABILITY		CE	
	CE MARK RATING		Dfl, S1	Dfl, S1
	HOT METAL NUT TEST	BS4790	Pass - Low radius of ignition	Pass - Low radius of ignition
	METHENAMINE PILL TEST	ISO 6925	Pass	Pass
	CHEMICAL IMPACT		CE	
	FORMALDEHYDE		E1	E1
	REACH CERTIFICATE		Compliant	Compliant
	BIOLOGICAL ATTACK			
	MOTH / INSECT RESISTANT		Eulan Treated	Eulan Treated

GENERAL INFORMATION

Installation - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

Maintenance - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. Loop pile carpets should be vacuumed with a cylinder cleaner or suction head only. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear. These areas will appear lighter or shaded in comparison to the less

frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Occasionally wool may contain traces of the sheep's natural environment. These traces can be easily removed and do not effect the durability of the carpet. Joins in loop pile carpet can sometimes be visible, especially so in patterned loop pile. The use of seaming cement is advisable.

Matching - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

Important - Minimum order length is 1.5 metres.

Greenwood & Coope Ltd | Brookhouse Mill, Greenmount, Bury, Lancashire, BL8 4HR
T: 01204 881234 | F: 01204 887722 | info@cormarcarpets.co.uk | www.cormarcarpets.co.uk

April 2019