



VersaShield meets or exceeds all Type II requirements of CCC-W-408A/D and W-101

**Specifications: Performance:**

Weight (Avg):	20 oz/ly (452 g/m <sup>2</sup> )
Thickness:	.016 average
Width:	52/54" (132/137 cm)
Backing:	Osnaburg
Packaging:	30 yd bolts

**Fire Safety:**

- Class A ASTM-E-84(GRC)
- NFPA 101 Life Safety Code
- CAN/ULC S102-18

**Features and Benefits:**

- Exceeds Type II performance standards
- Impervious to stains with superior cleanability
- Breaking Strength (lbs.) 80 x 80
- Tear Strength (lbs.) 65 x 60
- Ease of installation

**Environmental and Health:**

- Phthalate Free
- Health Product Declaration
- Meets State of Washington Bldg. Specification for Indoor Air Quality
- Meets California Section 01350 Indoor Air Quality Standard
- Aggressive manufacturing materials recovery and reuse program
- Printed with water-based inks
- Free of PBDE's (Brominated Flame Retardants)

**USGBC LEED Support:**

- Supports USGBC LEED v4.1 criteria
- Material and Resources; Building Product Disclosure and Optimization (includes Recycled Content, Construction Waste Management; HPD's)
- Indoor Environmental Quality: Low emitting materials

**Moisture, Mold and Mildew:**

Vinyl wall protection functions as a vapor barrier. If water or moisture becomes trapped between the wall protection and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wall protection products.

Visit [VersaWallProtection.com](http://VersaWallProtection.com) for complete specifications, installation instructions, cleaning directions and warranty.

**VERSA®**  
DESIGNED SURFACES

©VersaDesignedSurfaces

