

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
ACOUSTIC	VINACOUSTIC Katsura Reflect	FT N° 67

This is a PVC foam wallcovering that is dyed in the mass, micro-perforated, printed with water-based ink, on an Alpha 0.25 acoustic non-woven backing. Highly washable and brushable, resistant to impacts and scratches, this wall covering is particularly well-suited for intensive use in commercial and public establishments. In accordance with regulations, it has a M1 and Cs3 d0 fire rating. Quick and easy to hang by simply pasting on the wall and hanging the strips edge to edge.

Description

Item code KATR 9137 ...

Name Vinacoustic Katsura Reflect

Range Acoustic 03
Type PVC wallcovering
Plain Yes - 10 colours

Patterned No

Composition

Type Micro-perforated double vinyl coating, impregnated dye-method

Backing Acoustic non-woven polyester

Weight 890 g/m²
Thickness 3,5 mm

Ink Water-based printing inks

Treatment Bio-Pruf treatment on request > 500ml

Regulations - Environment

Fire rating C s3 d0 / M1 Standard EN 13 501 -1
Acoustics Alpha w 0,25 / NRC 0,25 Standard EN 20 354 / ASTM-C423-90a

Acoustics April w 0,25 / NRC 0,25 Standard EN 20 354 / AS INI-0425-90a Light fastness ≥ 6 Standard EN 259

Thermal resistance R = 0,08 m² K/W Standard EN 12 667

VOCs A+ ISO 16000

CE marking Yes Standard EN 15 102
Care Washable srubbable Standard EN 259

 Use
 Intensive
 Standard EN 259

 Breaking strength
 daN: L>35 / T>30
 ISO 1421

 Color fastness to rubbing
 dry 5/4 - wet 5/4
 NF ISO 105

Color fastness to rubbing
Certification
Manufactured by
Component

Color fastness to rubbing
dry 5/4 - wet 5/4
Oeko-tex standard 100
ISO 14001 / ISO 9002
Phtalate free PVC

Packing - Packaging

Size of widths +/- 1,30m

Length of roll 25ml - 15ml - 10ml - 5ml

Partial sale to order No
Dispenser box Yes FSC Certified Cardboard

Suspended core packaging Yes

Box size 1450 X 350 X3 50 cm = 25ml, 15ml / 1450 X 215 X 230 cm = 10ml Weight of a roll 31,22 Kg = 25ml, 19,65 Kg = 15ml, 13,87 Kg = 10ml. (+/- 10%)

Hanging operation

Adhesive Ovalit TM - Ovalit S (Metylan - Henkel)

Quantity of adhesive+/- 300-450 gr/m²MatchFree matchHanging directionStraight stripsSeamsEdge to edge seamsRemovalDampen before strippingFor partitionsYes - 130cm width

Demo video Yes

