

York Wallcovering

Tread Softly

Type II • 20 oz.

No Repeat – Random Match

Physical Properties:

Width: 54"/55.5"

Total Weight (oz./lin.yd): 20.3 oz.

Total Weight (oz./sq.yd): 13.0 oz.

Fabric Type: Nonwoven

Backing Fabric Weight: 1.8oz./sq.yard

Average Total Thickness: 16 mils

Custom put-ups available (Standard bolt size is 30-yards)

Federal Specifications:

- This wallcovering meets or exceeds all requirements of G.S.A. Federal Specification CCC-W-408A/D for Type 2 material.

Fire Hazard Classification Results:

Tested in accordance with ASTM E-84 Tunnel Test

Class A Fire Rated

Flame Spread: 15

Smoke Developed: 30

York Quality Standards

- LOW IN V.O.C.'s – Composite tested, low V.O.C. emitting vinyl wallcoverings
- ENERGY SAVINGS – Improves insulation R-factor by up to 6%
- ACOUSTICAL BENEFIT – N.R.C. rating of .10
- MILDEW RESISTANCE – Has best rating of 0 as tested in accordance with CCC-W-408A/D
- ENVIRONMENTALLY FRIENDLY – Low smoke, water based inks low in V.O.C.'s
- GLARE REDUCTION – Reflects significantly less light than commercial semi-gloss paint
- STAIN RESISTANCE - Yorkguard® Protective Coating

Environmental Statement:

York Wallcoverings has always sought to be a responsible neighbor as well as a steward of the earth's natural resources. York continues toward its goal of giving the healthcare, hospitality and corporate wallcovering users environmentally superior choices. We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.

Design Copyright © York Contract

