

# Specifications

---

**Versa PVC-FREE High Plains** pattern meets or exceeds all Type II requirements of CCC-W-408A/D and W-101.

---

<b>Specifications:</b>	<b>Performance:</b>
<b>Weight (Avg.):</b>	20 oz/ly (452 gr/m <sup>2</sup> )
<b>Content:</b>	Olefin Composite
<b>Width:</b>	52/54" (132/137 cm)
<b>Backing:</b>	Osnaburg
<b>Installation:</b>	Reverse hang / Straight across match

Custom colors, weights, widths and microventing are available.

---

#### Fire Safety:

- Class A - ASTM E-84 (GRC)
  - NFPA 101 Life Safety Code
  - CAN ULC/S102
- 

#### Environmental and Health:

- PVC-FREE
  - Phthalate Free
  - Health Product Declaration
  - Free of Antimicrobials
  - Meets State of Washington Building Specification for Indoor Air Quality
    - Meets California Section 01350 Indoor Air Quality Standard
  - Aggressive manufacturing materials recovery and reuse program
    - Highly cleanable water-based inks
  - Free of Halogenated flame retardants
    - 20% Recycled Content
    - Prop 65 Compliant
- 

#### USGBC LEED Support:

- Supports USGBC LEED v4.1 Criteria
  - Materials and Resources; Building Product Disclosure and Optimization (Includes Recycled Content; Construction Waste Management; HPD's)
    - Indoor Environmental Quality; Low emitting materials
- 

#### Moisture, Mold and Mildew:

Versa PVC-Free wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use and installation of vapor barriers.

---

#### Warranty:

**Versa PVC-FREE** is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Versa innovations, visit our website at [versapvcfreewallcovering.com](http://versapvcfreewallcovering.com).

## VERSA®

DESIGNED SURFACES

©Versa Designed Surfaces

