

Acoustic vinyl wallcovering – VINACOUSTIC Polyform 3

Description

This is an acoustic vinyl wallcovering that is dyed in the mass, micro-perforated, printed with water-based ink, coated on an acoustic non-woven backing. Alpha w 0.25 and NRC 0.25. Highly washable and brushable, resistant to impacts and scratches, this wall covering is particularly well-suited for intensive use in commercial and public establishments. In accordance with regulations, it has a M1 and Cs3 d0 fire rating. Quick and easy to hang by simply pasting on the wall and butted seams.

Item code	PFYR 9163...
Name	VINACOUSTIC Polyform 3
Range	Acoustic
Type	Acoustic vinyl wallcovering
Patterned	11 colours

Composition

Type	Micro-perforated double vinyl coating, impregnated dye-method
Backing	Acoustic non-woven polyester
Weight	890 g/m ²
Thickness	3,5 mm
Ink	Water-based printing inks
Treatment	Bio-Pruf treatment on request > 500ml

Regulations - Environment

Fire rating	C s3 d0 / M1	Standard EN 13 501 -1
Acoustics	Alpha w 0.25 / NRC 0.25	Standard EN 20 354 / ASTM-C423-90a
Light fastness	≥ 6 (1-8)	Standard EN 259
Thermal resistance	R = 0,08 m ² K/W	Standard EN 12 667
VOCs	A+	ISO 16000
CE marking	DoP-CPR-Vinacoustic / www.texdecor.com	Standard EN 15 102
Care	Extra washable and scrubbable	Standard EN 259
Use	Intensive	Standard EN 259
Breaking strength	daN : L>35 / T >30	ISO 1421
Color fastness to rubbing	dry 5/4 - wet 5/4 (1-5)	NF ISO 105
Certification	Oeko-tex standard 100	
Manufactured by	ISO 14001 / ISO 9002	
Component	Phthalate free PVC	

Packing - Packaging

Size of widths	+/- 1,25 m	
Length of roll	25ml - 15ml - 10ml	
Partial sale to order	No	
Dispenser box	Yes	FSC Certified Cardboard
Suspended core packaging	Yes	
Box size	1450 X 350 X 350 mm = 25ml ,15ml / 1450 X 215 X 230 mm = 10ml	
Weight of a roll	31.22 Kg = 25ml, 19.65 Kg = 15ml, 13.87 Kg = 10ml (+/- 10%)	

Hanging operation

Adhesive	Ovalit TM - Ovalit F (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	TM +/- 250 – F +/- 450 g/m ²
Match	Free match
Hanging direction	Straight strips
Seams	Butted seams
Removal	Dampen before stripping
For partitions	Yes
Hanging instructions	www.texdecor.com
Demonstration video	www.texdecor.com