

LINETEX

TECHNICAL SPECIFICATIONS

SECTOR

AUTOMOTIVE

- ✓ Caravans & RV
- ✓ General Automotive
- ✓ Mass Transportation
- ✓ Motorcycles

CONTRACT

- ✓ Healthcare
- ✓ Hospitality
- ✓ Office
- ✓ Outdoor
- ✓ Public Spaces
- ✓ Residential

MARINE

- ✓ Marine Exteriors
- ✓ Marine Interiors

DESIGN:

Textile

COMPOSITION:

Vinyl Topcoat

BACKING:

100% Polyester

PROTECTIVE FINISH



WIDTH:

137.00 cm

ROLL LENGTH:

30.00 m

WEIGHT:

665.00 gr/m2

FINISHES AND TREATMENTS

- UV Resistance: ISO 105 B04 \geq 4/5 (Grey Scale)
- UV-resistance: ISO 105 B02 \geq 7/8 (Blue Wool Scale)
- PERMACOOL
- PERMABLOK3® PLUS
- >100.000 cycles Martindale (EN ISO 12947:1999 Part 2)
- Cold Crack -29°C
- Anti-stain Finish
- Mildew resistant backing and face
- Sulfide Stain Resistant
- Anti-static Finish

WARRANTY

- 5 Years

FLAME RETARDANCY ¹

- EU: EN 1021 Part 1 & 2
- DE: DIN 4102 B2
- IMO FTP 2010 Code MSC.307 (88) Part 8 3.1 & 3.2
- (MED) Marine Equipment Directive (in its current valid version)
- US: NFPA 260 - Class 1
- US: CAL TB 117-2013, Section E
- US: FMVSS 302

¹ This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

