Specifications

VERSA Avenir pattern meets or exceeds all Type II requirements of CCC-W-408A/D and W-101.

| Specifications: Weight (Avg.): Width: Backing: Installation: Custom colors, weights, width | 52/54" (132/137 cm) |
|--|---------------------|
| Fire Safety: Iass A - ASTM E-84 (<i>GRC</i>) asses NFPA 286 Corner Burn* FPA 101 Life Safety Code AN/ULC S102-03* * ot available for Mylar Skus | |
| Environmental and Health: • hthalate Free • Health Product Declaration • Environmental Product Declaration • eets State of Washington Building Specification for Indoor Air Quality • eets California Section 01350 Indoor Air Quality Standard • ggressive manufacturing materials recovery and reuse program • Highly cleanable water-based inks • ree of PBDE's (Brominated Flame Retardants) | |
| | |

USGBC LEED Support:

 upports USGBC LEED v4.1 Criteria
aterials and Resources; Building Product Disclosure and Optimization (Includes Recycled Content; Construction Waste Management; HPD's)

ndoor Environmental Quality; Low emitting materials

Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

Further protection against mold growth may be achieved with Versa Permavent[®], a unique microventing technology that literally "breathes," helping manage the mobile moisture in walls.

Warranty:

VERSA is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Versa innovations, visit our website at versawallcovering.com.



©Versa Designed Surfaces

