

TECHNICAL DATA SHEET

MADIKERI

CONTRACT VINYL WALLCOVERING

Description

This is a through-coloured PVC wallcovering phthalate free, printed using water-based inks, on a high-tear non-woven backing. Extra washable and impact resistant, this Type II vinyl is suitable for intensive use in public buildings. In line with regulations, it has B s2 d0 / Class A fire resistance rating. Quick and easy to hang, simply paste the wall and butted seams.

Composition

Type	Compact PVC phthalate free / Vinyl Type II
Backing	High-tear non-woven backing
Weight	470 g/m ²
Thickness	0.55 mm
Ink	Water-based printing inks

Regulations – Environment

Fire rating	B s2 d0 / Class A	EN 13501 / ASTM E-84
	IMO	FTP CODE 2010 part 5
Acoustics	Alpha w 0.10 according to the substrate / acoustic report: PEUTZ - N°A3151	
Light fastness	≥ 7 (1-8)	ISO 105
VOCs	A+	ISO 16000
CE marking	DOP-CPR-VIGD-14 / www.texdecor.com	Norme EN 15 102
Manufactured by	ISO 9001	
Component	PVC with no phthalate	
Care	Extra washable - scrubbable	Standard EN 259
Use	Intensive / Vinyl Type II classification	Standard EN 259 / CCC-W-408D

Packing – Packaging

Size of width	106 cm +/- 3%
Length of roll	25 lm
Partial sale to order	Yes
Box size	145 X 21,5 X 23 cm = 25 ml
Weight of a roll	13 Kg (+/- 10%)

Hanging

Adhesive	Ovalit TM (Metylan HENKEL)	MSDS available
Adhesive instructions	Apply to the wall, using a roller	
Quantity of adhesive	+/- 150-200 gr/m ²	
Match	Plain : free match	
Seam	Butted seams or double cut overlap	
Removal	Pelable	