

TECHNICAL DATA SHEET

COMMERCIAL WALLCOVERINGS 20 OZ VOL.1

Fabric Backed Vinyl Wallcoverings

Specifications:

- Type II, 20 oz /yard, 450 g/m²
- Width: 132cm - 137cm
- Roll Length: 30m

Fire Safety:

- ASTM E84 - Class A
- CAN/ULC - S102

Environmental & Health:

- CA 01350 - Low Emitting Materials
- French VOC Emissions - Class A+
- California Proposition 65 - Compliant
- EN 15102 - Compliant
- REACH - Compliant (SVHC Substances Controlled)



Composition:

- PVC Film | Scrim / Non-Woven Backing | Water-Based Ink

Water Vapor Transmission

- According to the results of the ASTM E96 test result, the micro-vented fabric-backed wallcoverings exhibit excellent breathability.

Installation Instructions

- Hang first strip within 12 min to a plumb line, overlapping ceiling/baseboard.
- Smooth from center out using a stiff brush or plastic smoother (light pressure).
- Trim top and bottom with a sharp blade.
- Butt seams for matched patterns.
- For non-matching or free designs, overlap 2-3 inches and double-cut with a backing strip.
- Clean excess paste immediately with a damp sponge; dry with a lint-free cloth.
- Keep vertical seams at least 6 inches from corners.
- Avoid narrow strips above or below openings.
- After installation, check for moisture or vapor infiltration and correct promptly.