

TECHNICAL DATA SHEET

VERSACE 6

Product Description

Manufacturer

A.S. Création Tapeten AG
Südstr. 47
51645 Gummersbach
www.as-creation.de

Product Name

Versace 4

Product Features / Components

- Versace 4 Collection products are manufactured from the following resources:
 - Backing material: 90 g/m² non-woven (certified according to FSC)
 - Coating: approx. 280 g/m² PVC-Plastisol (all components are REACH compliant)
 - PVC 30 – 65%
 - DINP 15 – 40%
 - CaCO₃ 0 – 20%
 - Pigments 0 – 25%
 - Additives 0 – 15%
 - Blowing Agents 0 – 5%
- Versace 4 Collection non-woven wallcoverings do not need soaking time and can be hung using paste-the-wall technique or with a pasting machine.
- Versace 4 Collection non-woven wallcoverings can be completely dry-stripped if the surface has been suitably prepared.
- Versace 4 Collection non-woven wallcoverings are:
 - Skin-friendly, because they do not contain glass fibres
 - Dimensionally stable - therefore no soaking time required
 - Crack-bridging
 - Permeable to steam
 - Heavy flammable according to EN 13501-1. Can be used in the commercial sector

Technical Data

- Dimensions: wallcovering: 10.05 m x 0.70m; possible dimensional variations of + / - 3%
- Weight: ca 2,340 g – 2,670 g, depending on design, structure, composition and colour of the individual product
- Roll diameter: approx. 8.5 cm - 9 cm
- Hanging at 18°C and a relative humidity of 65% is ideal
- Drying time: 1-2 days, depending on the temperature, relative humidity and the base surface
- Permeable to steam according to DIN 53122 and DIN 52615
- In combination with mineral surfaces and non-combustible building panels it is flame-retardant according to EN 13501-1
- Rolls must be stored vertically in a dry, cool place
- Owing to batch production of wallpapers, only one fabrication can be processed in each area